RemoteHAMs K3S P3 S-BOX KPA1500

COMx (Ctrl)   USB
  DTR=CW
  RTS=RCForb PWR ON
COMy (MMTTY)
  PC

SM-8

S-BOX *

PC	FSK	SM-8	K3
RS232	DE9F	DE9F	ACC
DE9F			DE15F
Radio	FSK	PTT		PWR
RS232	OUT	OUT	n.c	ON
DE9M	RCA	RCA	RCA	RCA

AUX   USB
DE15F

KPA1500 AMP

DE-15M/M 5 ft
All 15 lines

Elecraft KPAK3AUX
DE-15 M/F Amp. Cable
(n.c. on pins 1, 4, 8)

PC-DE9F

XCVR-DE9M

12V
P3 Scope

Y-Cable / Splitter (or Y-BOX)
Dual DE-15F to DE-15M
All 15 lines wired

RS232/P3	12VDC	ACC
RJ45	OUT	DE15F
	RCA	

Elecraft K3S Transceiver

* **RTS** (pin 7) of PC RS232 **powers ON** K3S
  using RCForb opt. "Use RTS as Power"
  (S-BOX keying ckt wired to K3S ACC pin 8)

ACC Pin 1 = FSK, ACC Pin 4 = PTT IN

KPA1500 Utility powers KPA1500 **ON/OFF**